

## EVE - ER Battery Series

Li-SOCl<sub>2</sub>

Lithium batteries of EVE Battery



Type	Voltage	Nom. capacity *	Max. cont. current	Temperature range	∅ Dimensions	Construction
ER 14250	3,6 V	1,20 Ah	0,50 / 15,00 mA	-60°C - +85°C	14,50 x 25,40 mm	Cylindrical, bobbin electrodes
ER 14335	3,6 V	1,65 Ah	1,30 / 75,00 mA	-60°C - +85°C	14,50 x 33,50 mm	Cylindrical, bobbin electrodes
ER 14505	3,6 V	2,70 Ah	1,00 / 40,00 mA	-60°C - +85°C	14,50 x 50,50 mm	Cylindrical, bobbin electrodes
ER 17505	3,6 V	3,60 Ah	3,00 / 130,00 mA	-60°C - +85°C	17,50 x 50,50 mm	Cylindrical, bobbin electrodes
ER 18505	3,6 V	4,00 Ah	3,00 / 130,00 mA	-60°C - +85°C	18,70 x 50,50 mm	Cylindrical, bobbin electrodes
ER 26500	3,6 V	8,50 Ah	3,00 / 150,00 mA	-60°C - +85°C	26,20 x 50,00 mm	Cylindrical, bobbin electrodes
ER 34615	3,6 V	19,00 Ah	2,00 / 100,00 mA	-60°C - +85°C	33,10 x 61,50 mm	Cylindrical, bobbin electrodes
ER 341245	3,6 V	35,00 Ah	10,00 / 420,00 mA	-60°C - +85°C	32,9 x 124,50 mm	Cylindrical, bobbin electrodes

\* capacity under nominal discharge current, at temp. +25°C