

## CR Panasonic Series

CR cells - cylindrical construction

Panasonic Lithium Batteries



Type	Voltage	Nom. capacity	Max. cont. current **	Temperature range	⊗ Dimensions / Weight
CR-AAU	3,0 V	1800 mAh	2,50 / 1000 mA	-40°C - +85°C	14,5 x 50,5 mm / 19 g
CR-AAK	3,0 V	1650 mAh	2,50 / 1000 mA	-40°C - +85°C	14,5 x 50,5 mm / 19 g
CR-2Z	3,0 V	1000 mAh	2,50 / 1000 mA	-40°C - +75°C	15,6 x 27,0 mm / 11 g
CR-2U	3,0 V	1000 mAh	2,50 / 1000 mA	-40°C - +70°C	15,6 x 27,0 mm / 11 g
CR-2/3AZ	3,0 V	1600 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 33,5 mm / 17 g
CR-2/3AK	3,0 V	1400 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 33,5 mm / 17 g
CR-2/3	3,0 V	1400 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 33,5 mm / 17 g
CR-AG	3,0 V	2400 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 45,5 mm / 22 g
CR-AGZ	3,0 V	2700 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 45,5 mm / 22 g
CR-CZ	3,0 V	6500 mAh	2,50 / 1000 mA	-40°C - +70°C	26,0 x 50,5 mm / 60 g
2CR-5 *	6,0 V	1400 mAh	2,50 / 1000 mA	-40°C - +70°C	34,0 x 17,0 x 45,0 mm / 38 g
CR-123A	3,0 V	1400 mAh	2,50 / 1000 mA	-40°C - +70°C	17,0 x 34,5 mm / 17 g
CR-2	3,0 V	850 mAh	2,50 / 1000 mA	-40°C - +70°C	15,6 x 27,0 mm / 11 g
CR-P2 *	6,0 V	1400 mAh	2,50 / 1000 mA	-40°C - +70°C	35,0 x 19,5 x 36,0 mm / 37 g
CR-V3 *	3,0 V	3300 mAh	20,0 / 2000 mA	-40°C - +70°C	14,4 x 28,4 x 52,0 mm / 39 g

\* two-cell batteries

\*\* higher pulse currents possible

**GIVING IDEAS  
A FORM**